

Item
3713


1. Product description:

Straight Sanding Cartridge

Dimensions (in):	1/2" x 1-1/2" x 1/8"
Dimensions (mm):	13 x 38 x 3.2
Abrasive:	Ceramic
Grit:	60
Specification:	TTG5T - 60
Backing:	T Cotton
Structure:	Semi-open coat
Optimal RPM:	12,000
Max. rpm:	15,000



CLR



D= 13 mm
T = 38 mm
H = 3.2 mm



1. Aplicación

- For grinding and deburring metals, stainless steel, non-ferrous metals, superalloys, and aluminum.
- Ideal for small areas, holes, or hard-to-reach zones such as corners, internal areas, small radii, blind holes, and operations where larger tools cannot fit.
- Their geometry allows them to work inside, outside, on, and around workpieces.
- Provides high precision in high-performance operations.
- The abrasive grain composition also delivers strong sanding performance and long service life.
- The optimized self-sharpening effect enables high stock removal rates through continuous regeneration of sharp grain edges.

2. Operating instructions

- Use with a rotary tool.
- Use adapter item no. 1623.
- Mount the cartridge and let it run idle for one minute to ensure it is not damaged.
- Do not apply excessive pressure or subject it to impact against the workpiece.



Rotary Tool

3. Safety information

- Never exceed the maximum speed indicated on the label.
- Always use full personal protective equipment (gloves, hearing protection, mask, and safety glasses).
- Improper use may cause severe injury.

4. Handling

- Initial inspection must be carried out in the original packaging. If there is visible damage to the packaging, the product should not be accepted.
- Packages must not be exposed to hooks or sharp objects. They should not be stacked under excessive loads, as this may damage the product and cause breakage during use.

5. Storage

- All sanding products must be stored on pallets at least 10 cm above the floor, away from damp, cold, hot surfaces, or any type of fluid.
- Ideal storage conditions are 40–50% relative humidity and a temperature between 15 and 29 °C.

6. Packaging units

- 25 pieces.